

POLYGLOW LANDSCAPE FLOORING **for new and old surfaces**

Revolutionary, innovative GLOW system to create unique floorings for corridors, pedestrian areas, pathways or even for line marking or highlighting areas like stairs at fire exits or stairs etc.

Applied on all existing asphalt and concrete surfaces, marble or porous tile floorings in four to five layers with the parallel use of **GLOW.PRO GRANULES** and special, modified two-component PU, UV-resistant resins, **GLOW.PRO COATING G102**.

These modified resins let the final coating release the glow at night, during total dark or even in lighted areas but with the usage of our special black-light bulbs or spiral black-lights.

Steps :

1. Sanding of the rubber surface to achieve the proper adhesion with the glow coating(in some cases).
2. Priming of the surface with the **GLOW.PRO MODIFIED PRIMER G101**, two-component primer, in one layer with consumption of 0,2-0,25 kg per square meter.
3. Application by special airless spray of the **GLOW.PRO COATING G102** which consists of **GLOW.PRO SAND** and special, modified resin, in one or two layers.
4. Sealing of the **GLOW.PRO COATING G102** with the **GLOW.PRO SEALING COATING G103**, two-component coating, in two layers with total consumption of 0,4 kg per square meter, which helps the system to glow.

Application by airless or by rollers.