

POLYGLOW JOGGING TRACK for new surfaces

Revolutionary, innovative GLOW system for jogging tracks.

It is applied in six layers, after sanding the surface with the parallel use of **GLOW.PRO GRANULES** and **special, modified two-component PU, UV-resistant resins**.

These modified resins let the final coating release the glow at night, during total dark or even in lighted areas but with the usage of our special black-light bulbs or spiral black-lights.

Steps:

1. Preparation of the surface to achieve the proper adhesion with the glow coating.
2. Priming of the surface with the **GLOW.PRO MODIFIED PRIMER G101**, two-component primer, in one layer with consumption of 0,2-0,3 kg per square meter.
3. Application of a mixture of SBR granules and PU BINDER.
4. Application of the special polyurethane pore filler, **GLOW.PRO PORE FILLER G109**, to smooth out the surface.
5. Application of the **GLOW.PRO SEALING COATING G103**.
6. Application by airless spray of the **GLOW GRANULES**.
7. Sealing with the **GLOW.PRO SEALING COATING G103**, two-component coating, in two layers with total consumption of 0,4 kg per square meter, which helps the system to glow.

Application by airless or by rollers.

Jumeirah Lake Towers , Goldcrest executive tower, cluster C, office no 1502.

t: +971 4 430 9685, +971 4 430 9778

mail : eva@glowprocompany.com,

www.glowprocompany.com